



tasker®

...a project further...

NEW

New Special Accessories: Shrink tubes, Sleeves, Tape and Ties


1m heat - Shrink tubes 2:1

Code	Lenght (m)	Inner Diam. at delivery (mm)	Max Inner Diam. after heasting (mm)	Packaging (pc.)	Standard Colors	Colors on demand	Description
GTM1206	1	1,2	0,6	50	Colors: ● Black BK	Colors: ● Violet V	 <p>Guaina termorestringente in polietilene reticolata con fattore di restringimento 2:1. Ritardante la fiamma con temperatura operativa di -55/+125°C. UL/CSA Standard. Ideale per la realizzazione di cablati audio e video grazie alla sua estrema versatilità operativa.</p> <p> Shrink tube in cross-linked polyolefin with shrinkage factor of 2:1. Flame retardant with operative temperature of -55/+125°C. UL/CSA Standard. Ideal for audio and video wiring thanks to its extreme operational versatility.</p>
GTM1608	1	1,6	0,8	50	● Green G	● Brown BR	
GTM2412	1	2,4	1,2	50	● Blue B	● Grey GY	
GTM3216	1	3,2	1,6	50	○ White W	● Yellow/Green YG	
GTM4824	1	4,8	2,4	50	● Red R		
GTM6432	1	6,4	3,2	50	● Yellow Y		
GTM9548	1	9,5	4,8	50	● Orange O		
GTM1264	1	12,7	6,4	25	○ Transparent TR		
GTM1680	1	16,0	8,0	25			
GTM1995	1	19,0	9,5	25			
GTM2512	1	25,4	12,7	25			
GTM32016	1	32,0	16,0	10			
GTM3819	1	38,1	19,0	10			
GTM5025	1	50,8	25,4	5			

Heat - Shrink tubes 2:1 on Boxes

Code	Lenght (m)	Inner Diam. at delivery (mm)	Max Inner Diam. after heasting (mm)	Packaging (pc.)	Standard Colors	Colors on demand	Description
BOX1206		1,2	0,6	10	Colors: ● Black BK	Colors: ● Violet V	 <p>Guaina termorestringente in polietilene reticolata con fattore di restringimento 2:1. Ritardante la fiamma con temperatura operativa di -55/+125°C. UL/CSA Standard. Ideale per la realizzazione di cablati audio e video grazie alla sua estrema versatilità operativa.</p> <p>Shrink tube in cross-linked polyolefin with shrinkage factor of 2:1. Flame retardant with operative temperature of -55/+125°C. UL/CSA Standard. Ideal for audio and video wiring thanks to its extreme operational versatility.</p>
BOX1608		1,6	0,8	10	● Green G	● Brown BR	
BOX2412		2,4	1,2	10	● Blue B	● Grey GY	
BOX3216		3,2	1,6	10	○ White W	● Yellow Y	
BOX4824		4,8	2,4	10			
BOX6432		6,4	3,2	5			
BOX9548		9,5	4,8	5			
BOX1264		12,7	6,4	5			
BOX1680		16,0	8,0	5			
BOX1995		19,0	9,5	5			
BOX2512		25,4	12,7	5			

Heat - Shrink tubes 2:1 on Reels

Code	Lenght (m)	Inner Diam. at delivery (mm)	Max Inner Diam. after heasting (mm)	Packaging (pc.)	Standard Colors	Colors on demand	Description
GTB1206		1,2	0,6	150	Colors: ● Black BK	Colors: ● Violet V	 <p>Guaina termorestringente in polietilene reticolata con fattore di restringimento 2:1. Ritardante la fiamma con temperatura operativa di -55/+125°C. UL/CSA Standard. Ideale per la realizzazione di cablati audio e video grazie alla sua estrema versatilità operativa.</p> <p>Shrink tube in cross-linked polyolefin with shrinkage factor of 2:1. Flame retardant with operative temperature of -55/+125°C. UL/CSA Standard. Ideal for audio and video wiring thanks to its extreme operational versatility.</p>
GTB1608		1,6	0,8	150	● Green G	● Brown BR	
GTB2412		2,4	1,2	150	● Blue B	● Grey GY	
GTB3216		3,2	1,6	150	○ White W	● Yellow/Green YG	
GTB4824		4,8	2,4	75	● Red R		
GTB6432		6,4	3,2	75	● Yellow Y		
GTB9548		9,5	4,8	75	● Orange O		
GTB1264		12,7	6,4	50	○ Transparent TR		
GTB1680		16,0	8,0	50			
GTB1995		19,0	9,5	30			
GTB2512		25,4	12,7	30			
GTB32016		32,0	16,0	30			
GTB3819		38,1	19,0	30			
GTB5025		50,8	25,4	30			
GTB7638		76,2	38,1	15			
GTB10250		102,0	50,8	15			
GTB12663		126,0	63,5	15			
GTB15076		150,0	76,0	15			


tasker®

...a project further...


NEW

New Special Accessories: Shrink tubes, Sleeves, Tape and Ties


Braided Sleeves

Code	Min. Diam. (mm)	Inner Diam. at delivery (mm)	Max. Diam. (mm)	Packaging (m)	Standard Colors	Description
CTR8	5,0	8,0	12,0	100	Colors: ● Black	 <p>Calza trecciata in monofilamento di poliestere con resistenza alla trazione di 7000 kg/cm² e temperatura operativa di -50/+150°C. Ideale per contenere più cavi in un unico fascio o per la protezione di cablati.</p> <p>Monofilament polyester braided sleeve with tensile strength of 7000 kg/cm² and operating temperature of -50/+150°C. Ideal for holding multiple cables in a single bundle or for wired protection.</p>
CTR10	7,0	10,0	15,0	100	Code: BK	
CTR12	6,0	12,0	20,0	100		
CTR15	8,0	15,0	23,0	100		
CTR20	12,0	20,0	30,0	100		
CTR25	18,0	25,0	34,0	100		
CTR30	20,0	30,0	40,0	100		
CTR40	25,0	40,0	60,0	100		
CTR50	45,0	50,0	75,0	100		

Spiral Sleeves

Code	Min. Diam. (mm)	Inner Diam. at delivery (mm)	Max. Diam. (mm)	Packaging (m)	Standard Colors	Description
CSP8	7,5	8,5	60,0	10	Colors: ● Black	 <p>Calza a spirale in polietilene con temperatura operativa di -50/+85°C. Ideale per contenere più cavi in un unico fascio o per la protezione di cablati.</p> <p>Polyethylene spiral sleeves in with an operating temperature of -50/+85°C. Ideal for holding multiple cables in a single bundle or for wired protection.</p>
CSP10	9,0	10,2	65,0	10	Code: BK	
CSP13	12,0	13,0	70,0	10	○ Natural	
CSP16	15,0	16,4	100,0	10	NAT	

Velcro Tape

Code	Diam. (mm)	Packaging (m)	Standard Colors	Description
VEL12	12	25	Colors: ● Black	 <p>Nastro in velcro ad alta resistenza ideale per la realizzazione di cablati per le più svariate applicazioni operative.</p> <p>High resistance velcro tape ideal for the realization of premade cables for the most varied operative applications.</p>
VEL20	20	25	Code: BK	


tasker®

...a project further...


NEW

New Special Accessories: Shrink tubes, Sleeves, Tape and Ties


Cable Ties

Code	Length (mm)	Width (mm)	Max tightening Diam. (mm)	Weight hold (Kg)	Packaging (pc.)	Standard Colors	Colors on demand	Description
FST8024	80,0	2,4	15,0	8,0	100	Colors: ● Black ○ Natural	Code: BK NAT	 <p>Fascette in Nylon resistenti ai raggi UV e con temperatura operative di -40/+85°C. Autoestinguenti entro 30 sec. dall'incendio e Certificate UL, ideali per le più svariate applicazioni operative.</p> <p>UK Nylon cable ties, UV rays resistant with operating temperatures of -40/+85°C. Self-extinguishing within 30 sec. and UL certified. Suitable for different application.</p>
FST10025	100,0	2,5	22,0	8,1	100			
FST12025	120,0	2,5	30,0	8,1	100			
FST14025	140,0	2,5	33,0	8,1	100			
FST16025	160,0	2,5	40,0	8,1	100			
FST20025	200,0	2,5	53,0	8,1	100			
FST14036	140,0	3,6	33,0	18,2	100			
FST20036	200,0	3,6	53,0	18,2	100			
FST30036	300,0	3,6	76,0	18,2	100			
FST37036	370,0	3,6	102,0	18,2	100			
FST16048	160,0	4,8	38,0	22,2	100			
FST19048	190	4,8	46,0	22,2	100			
FST20048	200	4,8	50,0	22,2	100			
FST25048	250	4,8	60,0	22,2	100			
FST28048	280	4,8	70,0	22,2	100			
FST30048	300	4,8	76,0	22,2	100			
FST37048	370	4,8	102,0	22,2	100			
FST43048	430	4,8	110,0	22,2	100			
FST53048	530	4,8	140,0	22,2	100			

Adhesive bases for Cable Ties

Code	Racomanded ties width (mm)	Length (mm)	High (mm)	Housing thickness (mm)	Hole Diam. (mm)	Packaging (pc.)	Standard Colors	Description
BAD2,5	2,5	12,7	3,2	3,2	-	100	Colors: ● Black ○ Natural	 <p>Basette adesive in Nylon per fascette con temperatura operative di -40/+85°C. Autoestinguenti entro 30sec. dall'incendio e Certificate UL, ideali per le più svariate applicazioni operative.</p> <p>Nylon adhesive bases for cable ties, with operating temperatures of -40/+85°C. Self-extinguishing within 30 sec. and UL certified. Suitable for different application.</p>
BAD3,6	3,6	19,0	4,4	4,0	3,5	100		
BAD4,8	4,8	27,7	5,7	5,3	5,7	100		

Saddle support for Cable Ties

Code	Racomanded ties width (mm)	Length (mm)	Width (mm)	High (mm)	Hole Diam. (mm)	Packaging (pc.)	Standard Colors	Description
BSL3,7	4,8	14,9	9,5	7,2	3,7	100	Colors: ● Black ○ Natural	 <p>Supporti a sella in Nylon per fascette con temperatura operative di -40/+85°C. Autoestinguenti entro 30 sec. dall'incendio e Certificate UL, ideali per le più svariate applicazioni operative.</p> <p>Nylon saddle support for cable ties, with operating temperatures of -40/+85°C. Self-extinguishing within 30 sec. and UL Certified. Suitable for different application.</p>
BSL4,5	4,8	14,9	9,5	7,2	4,5	100		

Tools for Cable Ties

TFT1		Tira-fascette in metallo rosso per spessori fino a 4,8 mm con taglio automatico a fine regolazione.	Red metal Tie gun for thicknesses up to 4.8 mm with automatic cutting at the end of the adjustment.	TFT114		Tira-fascette in metallo rosso per spessori da 3,6 a 9,5 mm, con leva per il taglio manuale della fascetta a fine regolazione.	Red metal Tie gun for thicknesses from 3.6 to 9.5, with lever for manual cutting at the end of the adjustment.
------	---	---	---	--------	---	--	--