

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C257 – 4x0,22 mm² Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Premade Audio Quad Cables and Microphones.

- A:** Black Soft **PVC** Sheath. Outer cable Diam. Ø 5,50 (±0,20) mm.
- B:** Braided Shielding O.F.C. red copper covering 60%.
- C:** The cores are stranded in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Cores Insulation with compact PE. Colored White, Yellow, Red, and Green, Diam. Ø 1,20 (±0,20) mm.
- E:** Conductors in O.F.C. red copper with stranded formation 7x0,20 mm. Nom. Cross section 4x0,22 mm².

MARKING **tasker®** C257 4x0,22 mm² O.F.C. Shielded Audio Quad Cable.
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION or Metallic Armored.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	59 pF/mt
Capacity Core/Shield	106 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			