



Technical Datasheet

tasker® TSK 1050 CPR Cca – 2x0,35 mm² ✓RoHS₃

Low Capacity Balanced Microphone Cable – CPR Cca Class

tasker® TSK 1050 CPR Cca s1-d1-a3			
A	B	C	D

CATEGORY Balanced Microphone Cable (See News brochure)
APPLICATIONS Audio and Microphone on Fix Installation

- A:** Black **L.S.Z.H.** Sheath.
Outer cable Diam. Ø 6,20 (±0,20) mm.
- B:** Aluminum foil tape covering 100% + Stranded tinned copper drain wire
- C:** Cores insulation in **L.S.Z.H.**, colored one red and one white.
Diam. Ø 1,80 (±0,20) mm.
- D:** O.F. tinned copper formation 7x0,25 mm.
Nom. Cross section 2x0,35 mm².

MARKING **tasker®** TSK1050 CPR Cca - 2x0,35 mm² – Microphone Cable -
0987-CPR-723 – Cca – s1– d1–a3 – Firestop® - Halogen Free
- Made in Italy

Cable Properties

Conductor Resistance	56,50 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	92 pF/m
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 05.09.22
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			