

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

Firestop® tasker® C905 – Digital SAT 75Ω Cable Halogen Free



A	B	C	D	E
---	---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS SAT installations and video premade cables.

- A:** **L.S.Z.H.** Sheath. Flame Retardant and Halogen Free.
Available in different colors.
Outer cable diam. Ø 5,00 (±0,20) mm
- B:** First Shielding O.F.C. tinned copper Braid covering 40%
+ total taping in transparent polyester tape.
- C:** Second Shielding in Aluminum foil tape (Al/PET/Al), covering 100 %.
- D:** Core Insulation in Gas Injected Foam PEE. Diam. Ø 3,50 (±0,20) mm.
- E:** Stiff Wire in Red Copper - formation 1x0,80 mm.
Nom. Cross section 1x0,50 mm².

MARKING tasker® C 905 L.S.Z.H. Coax 75 Ohm GAS INJECTED - DIGITAL SAT EN 50117
 Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **PVC, PE, PUR,**
 with or without Metallic Armor.

Cable Properties

Conductor Resistance	38,00 Ω/Km
Capacity Core/Shield	53 pF/m
Velocity of Propagation	84%
Impedance	75 Ω
Operative Temperature	-30/+70°C

Attenuation Test (dB/100 m.)

50 MHz	5,9	1000 MHz	26,3
100 MHz	7,8	1350 MHz	30,8
200 MHz	11,3	1750 MHz	35,6
470 MHz	17,6	2150 MHz	40,0
800 MHz	23,0	2400 MHz	42,2
860 MHz	24,2	2700 MHz	45,2

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			