

Technical Datasheet

tasker® T19 – 2x19 AWG - Flexible Loudspeaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Loudspeakers and Electronics.

- A:** Black Soft PVC Sheath.
Outer cable Diam. Ø 6,00 (±0,20) mm.
- B:** Core Insulation with PVC, colored one Red and one Black.
Diam. Ø 2,10 (±0,20) mm.
- C:** O.F.C. red copper formation 24x0,20 mm.
Nom. Cross section 2x19 AWG.

MARKING **tasker® T19 2x19 AWG O.F.C. - Loudspeaker Cable - FirestoP® - Made In Italy**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**,
PRODUCTION **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	21,93 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 21.10.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			