

## Technical Datasheet

# tasker® C106 – 5x0,35 mm<sup>2</sup>

## Twisted Multi Conductor Cable



A

B

**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture does not represent the real number of conductors  
 Multi Conductor Cable (See Electronics Catalogue)  
 Electronics and Wiring.

- A:** The **PVC** conductors are twisted together to create the cable.  
 Outer Diam. Ø 4,70 (±0,20) mm.  
 Single Conductor Diam. Ø 1,80 (±0,20) mm.  
 Color Code: White, Pink, Light-Blue, Yellow, Bright-Orange.
- B:** O.F.C. Red Copper stranded formation with 0,20 mm elementary wires.  
 Nom. Cross section 5x0,35 mm<sup>2</sup>.

**MARKING** not marked

### Cable Properties

<b>Conductor Resistance</b>	58 Ω/Km
<b>Operating Voltage</b>	300V
<b>Min. Bending Radius</b>	3 x O.D.
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 15.04.26
		Outdoor	Esterno		<b>X</b>	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated