

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet **tasker® C408 – 8x2x0,22 mm²** **Single Shielded Multipair Audio Cable**

RoHS₂
 2002/95/EC
 2011/65/UE



CATEGORY Multipair Audio Cable (See Audio Catalogue)
APPLICATIONS Premade cables for audio mixers and stage boxes.

- A:** Black Soft **PVC** Sheath. Outer cable Diam. Ø 13,00 (±0,20) mm.
- B:** The single pair are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape. Nom. Ø 3,00 (±0,20) mm.
- C:** The single pair are shielded with spiral in O.F.C. red copper, covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **Solid PE**, colored one Yellow and one Transparent. Diam. Ø 1,00 (±0,20) mm.
- E:** O.F.C. red copper formation 28x0,10 mm. Nom. Cross section 8x2x0,22 mm².

MARKING **tasker® C408 8x2x22 mm² PROFESSIONAL MULTIPAIR CABLE FOR AUDIO MIXER MADE IN ITALY**

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	78,15 Ω/Km
Capacity Core/Core	75 pF/mt
Capacity Core/Shield	160 pF/mt
Velocity of Propagation	66%
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio
Impiego		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 16.05.16