

Technical Datasheet

tasker® TSK 1039 – 2x0,50 mm²

DMX Digital Audio 110 Ohm Cable AES/EBU

FirestoP®

RoHS₃



A

B

C

D

E

CATEGORY APPLICATIONS

Digital Audio Cable (See Audio Catalogue)

Digital Audio Applications and DMX Light

- A:** Soft **Flame Retardant PVC** available in different colors.
Outer cable Diam. Ø 6,60 (±0,20) mm.
- B:** Shielding O.F.C. tinned copper Braid covering 85% + O.F.C. tinned copper Drain Wire.
- C:** Waste filler between conductors and total taping in not woven polyester.
- D:** Core Insulation with **PPE**, colored one Red and one Blue.
Core Diam. Ø 2,00 (±0,20) mm.
- E:** O.F.C. tinned copper formation 16x0,20 mm.
Nom. Cross section 2x0,50 mm².

MARKING

tasker® TSK 1039 2x0,50 - 20 AWG O.F.C. Extra Flex Digital 110 Ω DMX Audio
Cable FirestoP® Italy

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, or Metallic Armored.

Cable Properties

Conductor Resistance	38,00 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	62 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			