



Technical Datasheet

tasker® C282 Super 8x4,00 mm² Special Speaker Cable



CATEGORY Speaker Cable (See News Brochure)
APPLICATIONS Professional Loudspeakers and premade cables for mobile use

- A:** Black PVC sheath.
Outer Diam. Ø 18,00 (±0,20) mm.
- B:** Core Insulation with PVC Sheaths, black and numbered.
Cores crown grouped around a central PE rigid filler end wrapped with not woven tape. Cores Diam. Ø 3,80 (±0,20) mm.
- C:** O.F.C. red copper extra flex formation 126x0,20 mm.
Nom. Cross section 8x4,00 mm².

MARKING tasker® C282 Super – 8x4,00 mm² - O.F.C. – Extra Flex Special Loudspeaker Cable – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PUR, with or without Metallic Armor.

Section A-A'



Cable Properties

Conductor Resistance	5,74 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio
Impiego		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
	X	Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS3 Compliant
Informazioni	X	Ver. C / 30.04.19