

MILAN S.r.l. a socio unico


Head Office – Export department:  
Viale Europa, 74  
20090 Cusago (MI) Italy  
T. +39 02 9039.4556-4158  
F. +39 02 9039.4551  
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione  
Viale Europa 72 Strada F12  
20090 Cusago (MI) Italy  
T. +39 02 9039.0037-0059  
F. +39 02 9039.0049  
www.tasker.it



## Technical Datasheet

### tasker® C12025 CPR – 12x0,25 mm<sup>2</sup> Braided Shielded Cable



**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture does not represent the real number of conductors  
Braided Conductor Shielded Cable (See Data Network Catalogue)  
Data transmission and Electronics

- A:** Black **Flame Retardant PVC** sheath.  
Outer cable diam. Ø 9,00 (±0,20) mm.
- B:** Braided Shielding O.F.C. Red Copper covering 85%.
- C:** Cores Insulation with **Flame Retardant PVC**.  
Core color code with DIN 47100 Standards.  
Diam. Ø 1,40 (±0,20) mm.
- D:** Stranded O.F.C. Red Copper formation 8x0,20 mm.  
Nom. Cross section 12x0,25 mm<sup>2</sup>.

**MARKING**

**tasker®** C12025 CPR 12x0,25 mm<sup>2</sup> O.F.C. - IMQ 0051-CPR-0966 – 2017 – Eca – 2661 - UKCA – 2022 - BRAIDED SHIELDED CABLE - Firestop® - Made Italy

**Cable Properties**

<b>Conductor Resistance</b>	75,85 Ω/Km
<b>Capacity Core/Core</b>	110 pF/m
<b>Capacity Core/Shield</b>	230 pF/m
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS3 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>		Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	UKCA Compliant
		Outdoor	Esterno			Mobile	Mobile		<b>X</b>	Ver. C / 30.08.22
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			