



MILAN S.r.l. a socio unico

Head Office – Export department:
Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it

Technical Datasheet

tasker® TSK408 CPR Cca – 2x8,00 mm²

Fix Installation Speaker Cable



A	B	C
---	---	---

CATEGORY Fix Installation Speaker Cable (See News brochure)
APPLICATIONS Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free. Outer cable Ø: 14,00 (±0,20) mm.
- B:** Core Insulation in **L.S.Z.H.**, colored one Red and one Black. Diam. Ø: 5,50 (±0,20) mm.
- C:** O.F.C. red copper formation 112x0,30 mm. Nom. Cross section 2x8,00 mm².

MARKING **tasker®** TSK408 CPR Cca - 2x8,00 mm² - Loudspeaker Cable -0987-CPR-721
- Cca – s1–d1-a3 – FirestopP® - Halogen Free – Made in Italy

NOTE The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

Cable Properties

Conductor Resistance	2,60 Ω/Km
Max Rated Voltage	100 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 22.01.24
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			