

Technical Datasheet

tasker® C202 Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Premade Cables and Small Microphones

- A:** Black Soft PVC Sheath.
Outer cable Diam. Ø: 3,00 (±0,20) mm.
- B:** Shielding in O.F.C. tinned copper spiral covering 100%.
- C:** Core Insulation with PVC, colored one Red and one White.
Diam. Ø: 0,90 (±0,10) mm.
- D:** O.F.C. tinned copper formation 12x0,10 mm.
Nom. Cross section 2x0,08 mm².

MARKING tasker® C 202 2x0,08 mm² O.F.C. Balanced Mini Microphone Cable
CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, or Metallic Armored.

Cable Properties

Conductor Resistance	203 Ω/Km
Capacity Core/Core	170 pF/m
Capacity Core/Shield	310 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			