

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

# tasker® C115 - 3x0,14 mm<sup>2</sup>

## Spiral Shielded Cable



**CATEGORY**      Spiral Shielded Cable (See Audio Catalogue)  
**APPLICATIONS**    Sound Reproductions and Electronics.

- A:**            Soft Black **PVC**.  
Outer Cable Diam. Ø 5,00 (±0,10) mm.
- B:**            The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:**            Core Insulation with PVC, colored Black, White and Red.  
Core Diam. Ø 1,30 (±0,10) mm.
- D:**            O.F.C. red copper stranded formation 18x0,10 mm.  
Nom. Cross section 3x0,14 mm<sup>2</sup>.

**MARKING**        **tasker®** C115 3x0,14 mm<sup>2</sup> O.F.C. Individually Shielded Cable  
**CUSTOM**        This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**  
**PRODUCTION**    or Metallic Armored.

### Cable Properties

<b>Conductor Resistance</b>	138 Ω/Km
<b>Capacity Core/Core</b>	150 pF/mt
<b>Capacity Core/Shield</b>	290 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			