

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® RG 223U - Mil. C 17 F Standard

Silver Plated Coaxial Cable 50 Ω



A	B	C	D	E
---	---	---	---	---

CATEGORY RF Coaxial cable 50 Ω (See General Catalogue)
APPLICATION RF antenna and 50Ω premade cables

- A:** PVC black Sheath. - Outer cable Diam. Ø 5,40 (±0,20) mm.
- B:** First Shielding in **Silver Plated Copper** Braid covering 98%.
- C:** Second Shielding in **Silver Plated Copper** Braid covering 97%.
- D:** Core Insulation with transparent compact PE Ø 3,00 (±0,20) mm.
- E:** Stiff Wire in **Silver Plated Copper** formation 1x0,90 mm.
Nom. Cross section 1x0,63 mm².

MARKING tasker® RG 223 U MIL- C-17F 50 OHM DOUBLE SHIELD Made in Italy
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	28 Ω/Km
Capacity Core/Shield	100 pF/m
Velocity of Propagation	66%
Impedance	50 Ω
Voltage	2.000 V
Operative Temperature	-30/+70°C

Attenuation Losses dB/100 m

Frequency	dB	Max Watt (W)	Frequency	dB	Max Watt (W)
50 MHz	9,20	358	1000 MHz	47,40	80
100 MHz	16,00	207	1500 MHz	60,50	65
500 MHz	30,00	119	2000 MHz	72,20	57
600 MHz	35,40	103	2500 MHz	82,60	51
800 MHz	41,60	89	3000 MHz	90,50	46

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 17.06.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			