

## Technical Datasheet

# tasker® C181 - 5x0,14 mm<sup>2</sup>

## Spiral Shielded Cable



A	B	C	D
---	---	---	---

**NOTE**  
**CATEGORY**  
**APPLICATIONS**

The picture don't represent the real number of conductors.  
 Spiral Shielded Cable (See Audio Catalogue)  
 Sound Reproductions and Electronics.

- A:** Soft Black PVC.  
Outer Cable Diam. Ø 6,50 (±0,10) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored Black, White, Red, Yellow, Green.  
Core Diam. Ø 1,30 (±0,10) mm.
- D:** O.F.C. red copper stranded formation 18x0,10 mm.  
Nom. Cross section 5x0,14 mm<sup>2</sup>.

**MARKING**  
**CUSTOM**  
**PRODUCTION**

**tasker® C181 5x0,14 mm<sup>2</sup> O.F.C. Individually Shielded Cable**  
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,** or Metallic Armored.

**Cable Properties**

<b>Conductor Resistance</b>	138 Ω/Km
<b>Capacity Core/Core</b>	150 pF/m
<b>Capacity Core/Shield</b>	370 pF/m
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-15/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. B / 26.05.26
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			