

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

tasker® T31 Extra Flex Balanced Microphone Cable



A	B	C	D
---	---	---	---

CATEGORY
APPLICATIONS

Balanced Microphone Cable (See News Brochure)
 Premade Audio Cables and Microphones.

- A:** Black Soft **PVC** sheath. Outer Diam. Ø 6,50 (±0,10) mm.
- B:** Shielding in O.F.C. red copper Spiral covering 75 % + O.F.C. Tinned copper Drain Wire.
- C:** Core Insulation with a solid PE, colored one Red and one Transparent. Diam. Ø 1,20 (±0,10) mm.
- D:** O.F.C. red copper formation 28x0,10 mm. Nom. Cross section 2x0,22 mm².

MARKING

tasker® T31 2x0,22 mm² O.F.C. EXTRA FLEX LOW CAPACITANCE MULTILINE AUDIO CABLE MADE IN ITALY

CUSTOM
PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	75 pF/mt
Capacity Core/Shield	160 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 18.10.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			