

Technical Datasheet

tasker® C850 – 2x0,22 mm²



Silver Plated DMX Digital Audio 110 Ohm Cable AES/EBU



A

B

C

D

E

CATEGORY Digital Audio Cable (See Audio Catalogue)
APPLICATIONS Professional Digital Audio Applications and DMX Light

- A:** Grey PVC sheath.
Outer cable Diam. Ø 6,00 (±0,20) mm.
- B:** S.P.C. Silver Plated Copper Braid Shielding covering 95%
+ O.F.C. tinned copper Drain Wire.
- C:** Waste filler between conductors and total taping in not woven polyester.
- D:** Core Insulation with PPE, colored one Red and one Blue.
Core Diam. Ø 1,50 (±0,20) mm.
- E:** S.P.C. Silver Plated Copper formation 11x0,16 mm.
Nom. Cross section 2x0,22 mm².

MARKING **tasker®** C850 1x2x24 AWG AES/EBU 110 Ω Digital Silver Cable
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**,
PRODUCTION **PUR**, or Metallic Armored.

Cable Properties

Conductor Resistance	79,15 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	62 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			