

Technical Datasheet

tasker® C111 – 12x0,35 mm²

Twisted Multi Conductor Cable



A

B

NOTE
CATEGORY
APPLICATIONS

The picture does not represent the real number of conductors
 Multi Conductor Cable (See Electronics Catalogue)
 Wiring and Electronics.

- A:** The PVC conductors are twisted together to create the cable.
 Outer Diam. Ø 6,90 (±0,20) mm.
 Single Conductor Diam. Ø 1,80 (±0,20) mm.
 Color code: White, Pink, Light-Blue, Yellow, Orange, Grey, Green,
 Red, Violet, Blue, Brown, Black.
- B:** Stranded O.F.C. Red Copper formation realized with 0,20 mm elementary
 wires. Nom. Cross section 12x0,35 mm².

MARKING
CUSTOM
PRODUCTION

Cable not marked
 This product may be custom produced also in L.S.Z.H. polymer, PE, PUR.

Cable Properties

Conductor Resistance	58 Ω/Km
Operating Voltage	300V
Min. Bending Radius	3 x O.D.
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 15.04.26
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated