

MILAN S.r.l. a socio unico


Head Office – Export department:
Viale Europa, 74
20090 Cusago (MI) Italy
T. +39 02 9039.4556-4158
F. +39 02 9039.4551
www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
Viale Europa 72 Strada F12
20090 Cusago (MI) Italy
T. +39 02 9039.0037-0059
F. +39 02 9039.0049
www.tasker.it



Technical Datasheet

tasker® C3025 CPR – 3x0,25 mm² Braided Shielded Cable



NOTE
CATEGORY
APPLICATIONS

The picture does not represent the real number of conductors
Braided Conductor Shielded Cable (See Data Network Catalogue)
Data transmission and Electronics

- A:** Black **Flame Retardant PVC** sheath.
Outer cable diam. Ø 5,00 (±0,20) mm.
- B:** Braided Shielding O.F.C. Red Copper covering 85%.
- C:** Cores Insulation with **Flame Retardant PVC**.
Core color code with DIN 47100 Standards.
Diam. Ø 1,40 (±0,20) mm.
- D:** Stranded O.F.C. Red Copper formation 8x0,20 mm.
Nom. Cross section 3x0,25 mm².

MARKING

tasker® C3025 CPR 3x0,25 mm² O.F.C. - IMQ 0051-CPR-0966 – 2017 – Eca –
2661 - UKCA – 2022 - BRAIDED SHIELDED CABLE - Firestop® - Made Italy

Cable Properties

Conductor Resistance	75,85 Ω/Km
Capacity Core/Core	150 pF/m
Capacity Core/Shield	290 pF/m
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	<input checked="" type="checkbox"/>	Indoor	Interno Edificio	INSTALLATION	<input checked="" type="checkbox"/>	Fixed	Fissa	INFORMATION	<input checked="" type="checkbox"/>	RoHS3 Compliant
Impiego	<input checked="" type="checkbox"/>	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	<input checked="" type="checkbox"/>	UKCA Compliant
		Outdoor	Esterno			Mobile	Mobile		<input checked="" type="checkbox"/>	Ver. C / 28.08.22
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			