

MILAN S.r.l. a socio Unico

Head Office - Export Department
Viale Europa, 74
20047 Cusago (MI) Italy
Tel. +39 02 9039.4556 - 4158
www.taskercables.com

Ufficio Commerciale e Distribuzione
Viale Europa, 72 Strada F12
20047 Cusago (MI) Italy
Tel. +39 02 9039.0037 - 0059
www.tasker.it

Capitale Sociale € 100.000,00 i.v.
Cod. Fisc. e RIVA/VAT Nr. IT 03835660154
RE.A. MI 975732 Reg. Imprese MI 178864-5179-14
PEC: taskerpec@legalmail.it

Technical Datasheet

tasker® RG 59 PUR 75 Ω

Coaxial Mil. C 17 F Standard Cable – Outdoor Use



A	B	C	D
---	---	---	---

CATEGORY
APPLICATIONS

Coaxial cable 75 Ω (See Video Catalogue)
Premade video Cables and Broadcast.

- A:** Black Polyurethane **PUR** Sheath. Outer Diam. Ø 6,40 (±0,20) mm
Flame Retardant, Halogen Free and UV, Water, Chemical and Oil Resistant.
- B:** Shielding O.F.C. red copper Braid covering 98%.
- C:** Core Insulation with transparent compact PE. Diam. Ø 3,70 (±0,20) mm.
- D:** Stiff Wire in CW Formation 1x0,58 mm.
Nom. Cross section 1x0,26 mm². (23 AWG).

MARKING

tasker® RG59 PUR 75 Ohm Mil. - C17/F Outdoor use video cable
– Made in Italy

AVAILABLE ALSO

RG59 BU, RG59 Flex, RG59 LSZH, RG59 Special, RG59 Extra, RG59 AR

CUSTOM PRODUCTION

This product may be custom produced also in **PE**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	158 Ω/Km
Capacity Core/Shield	67 pF/m
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Operative Temperature	-40/+80°C

Attenuation dB/100 m.

50 MHz	7,4
100 MHz	10,7
200 MHz	15,7
400 MHz	22,7
800 MHz	33,6
1000 MHz	38,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
	X	Outdoor	Esterno			Mobile	Mobile			
	X	Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			