

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

Firestop®

tasker® T26 16 + 13 AWG Flexible PVC Speaker Cable

✓
RoHS₂
 2002/95/EC
 2011/65/UE



A	B	C
---	---	---

CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional loudspeakers and premade cables

- A:** Black Soft **Flame Retardant PVC** Sheath.
 Outer cable Diam. Ø 9,40 (±0,20) mm.
- B:** Core Insulation with PVC Sheath.
 16 AWG Cores have diam. Ø 2,60 (±0,20) mm.
 and are colored one Red and one Black.
 13 AWG Cores have diam. Ø 3,20 (±0,20) mm.
 and are colored one Blue and one Green.
- C:** All conductors are made of O.F.C. red copper.
 16 AWG Cores have a stranded formation 28x0,25 mm.
 13 AWG Cores have a stranded formation 54x0,25 mm.

MARKING **tasker® T26 2x16 + 2x13 AWG O.F.C. Loudspeaker Cable - FirestoP®**
 - Made In Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

16 AWG Conductor Resistance	12,50 Ω/Km
13 AWG Conductor Resistance	6,41 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			