

Technical Datasheet

tasker® TSK804 – 4x2x0,14 mm²

Digital Audio Multipair Cable 110 Ohm AES/EBU



CATEGORY

Digital Multipair Audio Cable (See Audio Catalogue)

APPLICATIONS

Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Black **PVC** Sheath.
Outer cable Ø: 10,30 (±0,20) mm.
- B:** The single pairs are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape.
Diam. Ø 3,20 (±0,20) mm.
- C:** The single pair are shielded with aluminum tape covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **foam PE**, colored one white and one red, and wrapped with not weaved polyester base tape.
Diam. Ø 1,20 (±0,20) mm.
- E:** O.F.C. tinned copper formation 18x0,10 mm.
Nom. Cross section 4x2x0,14 mm².

MARKING

tasker® TSK 804 4x2x0,14 mm² - EXTRA FLEX DIGITAL AUDIO MULTIPAIR CABLE - MADE IN ITALY

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	138,00 Ω/Km	Impedance	110 Ω
Capacity Core/Core	50 pF/m	Max Rated Voltage	49 V
Capacity Core/Shield	100 pF/m	Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			