

MILAN S.r.l. a socio unico

**Head Office – Export department:**  
 Viale Europa, 74  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.4556-4158  
 F. +39 02 9039.4551  
 www.taskercables.com

**Ufficio Commerciale e Centro Distribuzione**  
 Viale Europa 72 Strada F12  
 20090 Cusago (MI) Italy  
 T. +39 02 9039.0037-0059  
 F. +39 02 9039.0049  
 www.tasker.it

## Technical Datasheet

**Firestop®**

—nightly blue®—

# tasker® TSK1033 – 2x0,22 mm<sup>2</sup> Special Microphone Cable



A	B	C	D	E
---	---	---	---	---

**CATEGORY** Microphone Cable (See Audio Catalogue)

**APPLICATIONS** Premade Audio Cables and Microphones.

- A:** Night Blue Soft **Flame Retardant PVC** sheath.  
Outer cable Diam. Ø 6,20 (±0,20) mm.
- B:** Shielding in O.F.C. red copper Spiral covering 100%.
- C:** Inner white sheath between conductors and shielding.
- D:** Core Insulation with a compact XLPE, colored one Red and one White.  
Core Diam. Ø 1,20 (±0,20) mm.
- E:** O.F.C. red copper formation 28x0,10 mm.  
Nom. Cross section 2x0,22 mm<sup>2</sup>.

**MARKING  
 CUSTOM  
 PRODUCTION**

**tasker® TSK1033 2x0,22 mm<sup>2</sup> Extra flex Microphone cable - Made in Italy**  
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR,**  
 or Metallic Armored.

### Cable Properties

<b>Conductor Resistance</b>	79,15 Ω/Km
<b>Capacity Core/Core</b>	70 pF/mt
<b>Capacity Core/Shield</b>	106 pF/mt
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>		Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 26.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			