

Technical Datasheet

tasker® TSK1038 CPR Cca – 2x0,35 mm² **DMX Digital Audio 110 Ohm Cable AES/EBU**



A	B	C	D
---	---	---	---

CATEGORY Digital Audio Cable (See News brochure)
APPLICATIONS Digital Audio application and DMX light on Fix Installation

- A:** Black L.S.Z.H. Sheath UV resistant.
Outer cable Diam. Ø 6,20 (±0,20) mm.
- B:** Braided Shielding O.F.C. tinned copper covering 85%
+ Aluminum foil tape.
- C:** The cores are stranded in a pair with two Flame Retardant PVC filler.
Cores insulation in Foam PE, colored one red and one blue.
Diam. Ø 2,00 (±0,20) mm.
- D:** O.F.C. tinned copper stranded formation 7x0,25 mm.
Nom. Cross section 2x0,35 mm².

MARKING **tasker®** TSK1038 CPR Cca - 2x0,35 mm² – 110Ω DMX Audio Cable
- 0987-CPR-722 – Cca – s1– d2–a3 – FirestoP® - Halogen Free
- Made in Italy

Cable Properties

Conductor Resistance	56,50 Ω/Km
Capacity Core/Core	46 pF/m
Capacity Core/Shield	92 pF/m
Impedance	110 Ω
Test Voltage	1500V
Max Rated Voltage	49 V
Min. Bend. Radius (Fix)	10 x O.D.
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 05.09.22
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			