

Technical Datasheet

tasker® T30 – 2x0,22 mm² Balanced Microphone Cable



A	B	C	D
---	---	---	---

CATEGORY Balanced Microphone Cable (See Audio Catalogue)

APPLICATIONS Premade Audio Cables and Audio Multiline.

- A:** Soft Black PVC Sheath. Outer cable Diam. Ø 5,80 (±0,20) mm.
- B:** Shielding O.F.C. red copper Spiral covering 100%.
+ Tinned Copper Drain Wire.
- C:** The cores will be stranded in a pair with textile waste filler between Conductors. Core Insulation with a compact XLPE, colored one Red and one Transparent. Diam. Ø 1,10 (±0,10) mm.
- D:** O.F.C. red copper, formation 28x0,10 mm.
Nom. Cross section 2x0,22 mm².

MARKING tasker® T30 2x0,22 mm² O.F.C. Extraflex Microphone Cable Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

Cable Properties

Conductor Resistance	79 Ω/Km
Capacity Core/Core	75 pF/m
Capacity Core/Shield	160 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			