

Technical Datasheet

tasker® C115 - 3x0,14 mm²

Spiral Shielded Cable



CATEGORY Spiral Shielded Cable (See Audio Catalogue)
APPLICATIONS Sound Reproductions and Electronics.

- A:** Black PVC. Diam. Ø 5,00 (±0,20) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored Black, White and Red.
Core Diam. Ø 1,30 (±0,20) mm.
- D:** O.F.C. red copper stranded formation 18x0,10 mm.
Nom. Cross section 3x0,14 mm².

MARKING tasker® C115 - 3x0,14 mm² - O.F.C. - Individually Shielded Cable
CUSTOM This product may be custom produced also in L.S.Z.H. polymer, PE, PUR,
PRODUCTION or Metallic Armored.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	150 pF/m
Capacity Core/Shield	290 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 26.05.25
		Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			