

Technical Datasheet

tasker® C102 – 2x0,75 mm²

Red and Black Flat Divisible Cable



CATEGORY Flexible Audio Cable (See Audio Catalogue)
APPLICATIONS Speaker and Home Theatre installation

A: Red and Black Soft **PVC** Sheath.
Outer cable dimension 2,20 x 4,50 (±0,20) mm.

B: Both conductors are made of O.F.C. Red Copper.
Formation with 0,20 mm wires.
Nominal cross section 2x0,75 mm².

MARKING Cable not Marked
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE** or **PUR**.
PRODUCTION

Conductors Properties

Conductor Resistance	21,93 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 16.05.19
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			