

Technical Datasheet

tasker® C269 – 8x2,50 mm²

Flexible PVC Speaker Cable



A

B

C

CATEGORY

Flexible Speaker Cable

APPLICATIONS

Professional Loudspeakers and premade cables

- A:** Black Soft PVC sheath. Outer Diam. Ø 14,50 (±0,20) mm.
- B:** Core Insulation with PVC Sheaths. Diam. Ø 3,50 (±0,20) mm.
Color Code:
- 1) Red 5) Yellow
 - 2) Black 6) Grey
 - 3) Blue 7) Brown
 - 4) Green 8) Orange
- C:** O.F.C. red copper formation 80x0,20 mm.
Nom. Cross section 8x2,50 mm².

MARKING

tasker® C269 - 8x2,50 mm² – O.F.C. - Loudspeakers Cable – Made in Italy

CUSTOM

This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

PRODUCTION

Cable Properties

Conductor Resistance	6,41 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			