

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

✓
 RoHS₂
 2002/95/EC
 2011/65/UE

tasker® C404 – 4x2x0,22 mm²

Single Shielded Multipair Audio Cable



CATEGORY Multipair Audio Cable (See Audio Catalogue)
APPLICATIONS Audio Mixers, Benches and Audio Balanced multi sockets.

- A:** Soft Black **PVC** Sheath. Outer cable Diam. Ø: 10,20 (±0,20) mm.
- B:** The single pair are isolated with black **PVC**, numbered from one to the number of elements and wrapped together with polyester base tape. Diam. Ø 3,00 (±0,20) mm.
- C:** The single pair are shielded with spiral in O.F.C. red copper, covering 100% + tinned copper Drain Wire.
- D:** The single cores are insulated with **Solid PE**, colored one Yellow and one Transparent, and wrapped with not weaved polyester base tape. Diam. Ø 1,00 (±0,20) mm.
- E:** O.F.C. red copper formation 28x0,10 mm. Nom. Cross section 4x2x0,22 mm².

MARKING **tasker®** 4x2x0,22mm² Professional Multipair Cable for Audio Mixer – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

| | |
|--------------------------------|------------|
| Conductor Resistance | 79,15 Ω/Km |
| Capacity Core/Core | 75 pF/m |
| Capacity Core/Shield | 160 pF/m |
| Velocity of Propagation | 66% |
| Max Rated Voltage | 49 V |
| Operative Temperature | -15/+70°C |

| | | | | | | | | | | |
|----------------|----------|-----------------------|-------------------|---------------------|----------|----------------------|------------------|---------------------|----------|-------------------|
| USE | X | Indoor | Interno Edificio | INSTALLATION | X | Fixed | Fissa | INFORMATION | X | RoHS2 Compliant |
| Impiego | | Outdoor Limited | Esterno Limitato | Posa | X | Restricted Mobile | Mobile Limitata | Informazioni | X | Ver. A / 16.05.16 |
| | | Outdoor | Esterno | | | Mobile | Mobile | | | |
| | | Outdoor Direct Burial | Esterno Interrato | | | Mobile in Drag Chain | Mobile in Catena | | | |