

Technical Datasheet

tasker® TSK78 – 2x4,00 mm²



Siliconic Flat Audio Divisible Cable for High Temperature



CATEGORY Flat Divisible Audio Cable
APPLICATIONS Medical, water park, beauty center, harsh environment and temperature

A: Extra Soft White Silicon Rubber sheath.
 Outer cable dimension 4,20x8,40 (±0,20) mm.

B: Both conductors in O.F.C. Tinned Copper.
 Stranded formation 56x0,30 mm.
 Nominal cross section 2x4,00 mm².

MARKING tasker® TSK78 - 2x4,00 mm² - O.F.C. – Siliconic Audio Cable - Temp.
 Range - 60/+180°C – Made in Italy

CUSTOM PRODUCTION This product may be custom produced also in L.S.Z.H. polymer, PE, PVC or PUR.

Conductors Properties

Conductor Resistance	5,09 Ω/Km
Operating Voltage	300 V
Min. Bending Radius	4xouter Ø
Operative Temperature	-60/+180°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 14.04.26
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			