


MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet


 RoHS₂
 2002/95/EC
 2011/65/UE

tasker® C112 – 2x0,35 mm² Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Pre Made Audio Cables and Microphones.

- A:** Black Soft **PVC** sheath. Outer Diam. Ø 6,30 (±0,10) mm.
- B:** Spiral Shielding O.F.C. tinned copper covering 100%
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.
- D:** Transparent Cores Insulation with compact PE.
Diam. 1,70 (±0,10) mm.
- E:** Stranded formation 11x0,20 mm, One conductor in O.F.C. red copper and one in O.F.C. tinned copper. Nom. cross section 2x0,35 mm².

MARKING **tasker® C 112 2X0,35 mm² O.F.C. FLEXIBLE MICROPHONE CABLE FirestoP®**
 CEI 20-22 II - MADE IN ITALY

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	28 Ω/Km
Capacity Core/Core	55 pF/mt
Capacity Core/Shield	92 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			