

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it



Technical Datasheet

Firestop® tasker® C226 LSZH Halogen Free

1x0,08 (75Ω) +2x0,50 mm² Special Video Cable



CATEGORY Special Video Cable 75Ω (See video Catalogue)
APPLICATIONS Video installations, Security and Video Cameras.

A: Black **L.S.Z.H.** Sheath. Flame Retardant and Halogen Free.
 Outer cable Diam. Ø 6,60 (± 0,10) mm.

75 Ω Video Coax:

B: Inner Sheath in **L.S.Z.H.** Sheath. Flame Retardant and Halogen Free.
 Diam. Ø 2,80 (± 0,10) mm.
C: Spiral Shielding in O.F.C. tinned Copper covering 100%.
D: Dielectric in white **PEE**. Diam. Ø 1,50 (± 0,10) mm.
E: Stranded O.F.C. red copper formation 10x0,10 mm.
 Nom. Cross section 1x0,08 mm²

Insulated cores:

F: Inner Sheaths in **L.S.Z.H.** Sheath. Flame Retardant and Halogen Free.
 Both Colored Black. Diam. Ø 1,90 (± 0,10) mm.
G: Stranded formations 16x0,20 mm, one conductor in O.F.C. tinned copper
 and one in red copper. Nom. Cross section 2x0,50 mm².

MARKING **tasker® C224 1x0,75 OHM + 2x0,22 ²mm O.F.C. Special Video Cable FirestopP®**
MADE IN ITALY

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

CUSTOM PRODUCTION

This product may be custom produced also in **PVC, PE, PUR,** with or without Metallic Armor.

Coaxial Properties

Insulated Conductors Resistance	38,00 Ω/Km
Coax Conductor Resistance	203 Ω/Km
Coax Capacity Core/Shield	67 pF/m
Coax Velocity of Propagation	66%
Coax Impedance	75 Ω
Max Rated Voltage	49V
Operative Temperature	-30/+70°C

Attenuation dB/100 m.

50 MHz	19,50
100 MHz	28,50
200 MHz	41,70
400 MHz	60,20
800 MHz	87,30
1000 MHz	103,00

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 26.05.17