

Technical Datasheet

tasker® TSK404 CPR Cca- 2x4,00 mm² Fix Installation Speaker Cable



CATEGORY Fix Installation Speaker Cable (See News brochure)
APPLICATIONS Professional Loudspeakers

- A:** Black **L.S.Z.H.** polymer grade M1. Flame Retardant and halogen Free.
Outer cable Ø: 10,00 (±0,20) mm.
- B:** Core Insulation in **L.S.Z.H.**, colored one Red and one Black. Diam. Ø: 4,00 (±0,20) mm.
- C:** O.F.C. red copper formation 56x0,30 mm.
Nom. Cross section 2x4,00 mm².

MARKING tasker® TSK404 CPR Cca - 2x4,00 mm² - Loudspeaker Cable - 0987-CPR-721
- Cca - s1-d1-a3 - Firestop® - Halogen Free - Made in Italy

NOTE The cables are suitable for application in the same conduit with circuits of electrical systems with rated voltage up to 400V to earth, typically 230/400V power systems.

Cable Properties

Conductor Resistance	4,95 Ω/Km
Max Rated Voltage	100 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 05.09.22
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			