

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com


Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C284 – 2x2x0,22 + 3x1,50 mm² Special DMX 110 Ohm Cable

Firestop®

RoHS₃



CATEGORY DMX Cable + Power (See Audio Catalogue)
APPLICATIONS Active Digital Audio Cables

- A:** Black **Flame Retardant PVC**.
Outer cable Diam. Ø 13,80 (±0,20) mm.
- B:** The single sheath are stranded with waste filler between conductors and wrapped with not woven polyester tape.

2x Digital Audio 110 Ohm Pairs:

- C:** Black **Flame Retardant PVC**.
Diam. Ø 4,00 (±0,20) mm.
- D:** Shielding O.F.C. red copper Spiral covering 100% + O.F.C. tinned copper Drain Wire.
- E:** Core Insulation with PEE, colored one Red and one Blue.
Diam. Ø 1,50 (±0,20) mm.
- F:** O.F.C. tinned copper formation 28x0,10 mm.
Nom. Cross section 1x2x0,22 mm².

Three Power Conductors:

- G:** Black **Flame Retardant PVC**.
Diam. Ø: 7,20 (±0,20) mm.



MILAN S.r.l. a socio unico

Head Office – Export department: **Ufficio Commerciale e Centro Distribuzione**
 Viale Europa, 74 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158 T. +39 02 9039.0037-0059
 F. +39 02 9039.4551 F. +39 02 9039.0049
 www.taskercables.com www.tasker.it

- H:** Core Insulation with, **Flame Retardant** colored:
 Brown, Blue and Yellow/Green. Diam. Ø 3,00 (±0,20) mm.
- I:** O.F.C. red copper formation 48x0,20 mm.
 Nom. Cross section 3x1,50 mm².

MARKING
CUSTOM
PRODUCTION

tasker® C 284 2x2x0,22 + 3x1,5 Digital DMX Cable FirestoP® ITALY
 This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PUR**,
 with or without Metallic Armor.

Cable Properties

Digital Audio Cables Resistance	79,15 Ω/Km
Power Conductor Resistance	12,50 Ω/Km
Capacity Core/Core	50 pF/m
Capacity Core/Shield	95 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			