

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® C260 – 2x0,25 mm²

Low Capacity Balanced Microphone Cable



CATEGORY Balanced Microphone Cable (See Audio Catalogue)
APPLICATIONS Pre Made Audio Cables and Microphones.

- A:** **PVC Sheath.** Available in different color .
Outer cable Diam. Ø 6,00 (±0,20) mm.
- B:** **Shielding** O.F.C. red copper Spiral covering 100%.
- C:** **The cores are stranded** in a pair with textile waste filler between conductors and wrapped with not woven polyester based tape.
- D:** **Core Insulation** with a compact PE, colored one Orange and one Transparent. Diam. Ø 1,50 (±0,20) mm.
- E:** **O.F.C. red copper,** formation 8x0,20 mm.
Nom. Cross section 2x0,25 mm².

MARKING **tasker® C260 PROFESSIONAL NOISELESS MICROPHONE CABLE LOW CAPACITY**
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE,**
PRODUCTION **PUR,** with or without Metallic Armor.

Cable Properties

Conductor Resistance	75 Ω/Km
Capacity Core/Core	55 pF/mt
Capacity Core/Shield	90 pF/mt
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			