

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

FirestoP® tasker® RG 59 L.S.Z.H. RoHS₃

75 Ω Coaxial Mil. C 17 F Standard Cable – Outdoor Use



A	B	C	D
---	---	---	---

CATEGORY Coaxial cable 75 Ω (See Video Catalogue)
APPLICATIONS Standard definition video applications and cable assembly

- A:** Black L.S.Z.H. polymer Sheath grade M1 for Outdoor Use.
Flame Retardant and Halogen Free.
Outer Diam. Ø 6,30 (±0,20) mm.
- B:** Shielding O.F.C. red copper Braid covering 98%.
- C:** Core Insulation with transparent compact PE. Diam. Ø 3,70 (±0,20) mm
- D:** Stiff Wire in CW 1x0,58 mm.
Nom. Cross section 1x0,26 mm²

MARKING **tasker®** RG59 LSZH 75 Ohm Mil.- C17/F Coaxial Video Cable - FirestoP® - Halogen Free – Outdoor Use - Italy

CUSTOM This product is also available in other 8 different versions, among which PVC, PE, PUR, with or without Steel Armor

Cable Properties

Conductor Resistance	158 Ω/Km
Capacity Core/Shield	67 pF/m
Velocity of Propagation	66%
Impedance	75 Ω
Max Rated Voltage	2.000 V
Operative Temperature	-30/+70°C

Attenuation dB/100 m.

100 MHz	10,7
200 MHz	15,7
400 MHz	22,7
600 MHz	28,7
800 MHz	33,6
1000 MHz	38,0

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. B /23.05.19
	X	Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			