

Technical Datasheet

tasker® C724 S.-F.T.P. Cat. 8

Flex UL/ETL Standard Cable



CATEGORY High Frequency Transmission Data (See news Brochure)
APPLICATIONS LAN cabling, high frequency patch cord, Digital A/V over Cat. cables

- A:** Black **L.S.Z.H.** Sheath. Outer Diam. Ø 8,00 (±0,20) mm.
B: Al Braid shielding covering 85%
C: shielding with aluminum/polyester tape, covering 100%, on each single pairs.
D: Foam-skin polyethylene diam. 1,45 (±0,20) mm.
white-blue, white-orange, white-green, white-brown.
E: Stife wires O.F.C. Red Copper conductor 1x0,64 mm.
Nom. Cross section 4x2x0,34 mm².

MARKING **tasker®** C724 S-F.T.P. 4x2x0,35 mm² - CAT.8 – 100 Ω – ISO/IEC 11801
IEC 61156-6 EN50173 EN50288-10-1 IEC60332-2-1 – 10 GIGABIT ETHERNET
2000 MHz - FIRESTOP® - L.S.Z.H.

CUSTOM PRODUCTION This product may be custom produced also in **PUR** polymer, **PE**, **PVC**,
with or without Metallic Armor.

Cable Properties

Conductor Resistance	58 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-30/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 14.10.2024
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			