


Technical Datasheet



FirestoP®

tasker® FROR3100 – 3x1,00 mm²

Power Cable 450/750 V.



CATEGORY Power Cable (See Electronics Catalogue)
APPLICATIONS Energy and electrical installation.

- A:** Grey Flame Retardant **PVC** Sheath with reduced emission of corrosive Gases. Outer cable diam. Ø 9,10 (±0,20) mm.
- B:** Core Insulation with Flame Retardant **PVC** with reduced emission of corrosive Gases. Nom. Ø: 2,50 (±0,20) mm.
Color code: blue, brown, yellow/green.
- C:** O.F.C. red copper formation with 0,20 mm elementary wires.
Nom. Cross section 3x1,00 mm².

MARKING **tasker®** FROR 3100 3x1,00 Energy Cable - CEI 20-22/II IEMMEQU FROR 450/750V - 3x1,00 mm²

Cable Properties

Conductor Resistance	18,80 Ω/Km
Max Rated Voltage Uo/U	450/750 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio
Impiego	X	Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 16.05.17