

Technical Datasheet

tasker® C118 - 2x0,14 mm² - Shielded Flat Audio Cable



A	B	C	D
---	---	---	---

CATEGORY Shielded Flat Audio Cables (See Audio Catalogue)
APPLICATIONS Audio Premade Cable and head-phones.

- A:** PVC Sheath – Available in different colors.
Outer cable Dimensions 2,90x5,80 (±0,20) mm.
- B:** The single conductors are shielded with O.F.C. red copper spiral covering 100%.
- C:** Core Insulation with PVC, colored one Red and one Yellow.
Diam. Ø: 1,40 (±0,20) mm.
- D:** O.F.C. red copper formation 18x0,10 mm.
Nom. Cross section 2x0,14 mm².

MARKING tasker® C118 2x0,14 mm² O.F.C. Shielded Flat Cable
CUSTOM PRODUCTION This product may be custom produced also in LSZH polymer, PE or PUR.

Cable Properties

Conductor Resistance	138 Ω/Km
Capacity Core/Core	65 pF/m
Capacity Core/Shield	280 pF/m
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			