

## Technical Datasheet

### **tasker® C289 – 4x2,50 + 4x4,00 mm<sup>2</sup>**

### Flexible Speaker Cable



**CATEGORY** Flexible Speaker Cable (See Audio Catalogue)  
**APPLICATIONS** Professional loudspeakers and premade cables

- A:** Black PVC Sheath.  
Outer cable Diam. Ø 16,50 (±0,20) mm.
- B:** Core Insulation with PVC Sheath.  
Cores section 4x2,50 mm<sup>2</sup> have diam. Ø 3,50 (±0,20) mm.  
and are colored red, black, blue and green.  
Cores section 4x4,00 mm<sup>2</sup> have diam. Ø 4,20 (±0,20) mm.  
and are colored yellow, grey, brown and orange.
- C:** All conductors are made of O.F.C. red copper.  
Cores section 4x2,50 mm<sup>2</sup> have a stranded formation 80x0,20 mm.  
Cores section 4x4,00 mm<sup>2</sup> have a stranded formation 128x0,20 mm.

**MARKING** **tasker® C289 - 4x2,50+4x4,00 mm<sup>2</sup> – O.F.C. - Loudspeakers Cable**  
– Made in Italy

**CUSTOM PRODUCTION** This product may be custom produced also in L.S.Z.H. polymer, PE, PUR, with or without Metallic Armor.

#### Cable Properties

Sect. 2,50 mm <sup>2</sup> Conductor Resistance	6,41 Ω/Km
Sect. 4,00 mm <sup>2</sup> Conductor Resistance	4,31 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.17
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			