

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® TSK1171 – 4x0,50 mm²

Flat Divisible LED Cable



CATEGORY Flat Divisible LED Cable (See Electronics Catalogue)
APPLICATIONS Electronics and LED alimention

- A:** White **Flame Retardant PVC**. RAL 9010.
Outer cable dimension: 2,60x10,30 (±0,20) mm.
- B:** **HT105° PVC** insulation on each conductor.
Color Code: Red, Green, Blue, Black.
Outer cable Diam. Ø 1,50 (±0,20) mm.
- C:** Stranded O.F.C. red copper wire formation 16x0.20 mm.
Nom. Cross section 4x0,50 mm².

MARKING tasker® TSK1171 4x0,50 mm² O.F.C. Double Sheath Rgb-Led Strip Cable FirestoP®
CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**.

Properties

Conductor Resistance	38,00 Ω/Km
Rating Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 15.02.18
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			10% measurement tolerance, unless otherwise indicated