

Technical Datasheet

tasker® C702 Unshielded Twisted Pairs Cable



CATEGORY Unshielded Cable (See Data Network Catalogue)

APPLICATIONS Data transmission and electronics.

- A:** Grey Soft **PVC** Sheath.
Outer cable Diameter 4,50 (±0,20) mm.
- B:** The pairs are wrapped with transparent polyester tape.
- C:** The cores are insulated with PE – Diameter 0,90 (±0,20) mm.
The color code is:
1) White/Blue - Blue
2) White/Orange - Orange
- D:** Stiff Wire conductor in O.F.C. Red Copper.
Nominal cross section 2x2x0,22 mm², formation 1x0,51 mm.

MARKING **tasker® C702** – 2x2x0,22 mm² - O.F.C. – Unshielded Twisted Pair Cable –
Made In Italy

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
or Metallic Armored.

Cable Properties

Conductor Resistance	90 Ω/Km
Impedance	100 Ω
Max Rated Voltage	49 V
Operative Temperature	-15/+70°C

USE	X	Indoor	Interno Edificio
Impiego		Outdoor Limited	Esterno Limitato
		Outdoor	Esterno
		Outdoor Direct Burial	Esterno Interrato

INSTALLATION	X	Fixed	Fissa
Posa	X	Restricted Mobile	Mobile Limitata
		Mobile	Mobile
		Mobile in Drag Chain	Mobile in Catena

INFORMATION	X	RoHS2 Compliant
Informazioni	X	Ver. A / 26.05.17
10% measurement tolerance, unless otherwise indicated		