

Technical Datasheet

tasker® TSK101CPR – 2x16 AWG

Twisted Loudspeaker Cable for Fix Installation



CATEGORY Twisted Speaker Cable (See Audio Catalogue)
APPLICATIONS Loudspeaker cables for Fixed installation in constructions that require CPR certifications (not for power propose)

- A:** Tubular Black **Flame-retardant PVC AVML** Sheath.
Outer cable Diameter Ø 6,80 (±0,20) mm.
- B:** Core Insulation with **PE** Sheath, colored one Orange and one White.
Twist pitch of 60 mm. Core Diameter Ø 2,50 (±0,20) mm.
- C:** O.F.C. red copper formation 48x0,20 mm.
Nom. Cross section 2x16 AWG.

MARKING **tasker® TSK101 CPR 2x16 AWG O.F.C. – IMQ0051-CPR-1141 - 2017 – Eca –**
Twisted Speaker Cable for Fix Installation – FirestoP® - Made in Italy

Cable Properties

Conductor Resistance	12,50 Ω/Km
Max Rated Voltage	100 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa		Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. C / 05.09.24
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			