

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

FirestoP® tasker® TSK 1039 PUR -2x0,50 mm² Halogen Free

DMX Digital Audio 110 Ohm Cable AES/EBU – Outdoor Use



A | B | C | D | E

CATEGORY Digital Audio Cable (See Audio Catalogue)
APPLICATIONS Digital Audio Applications and DMX Light

- A:** Black **PUR** sheath. Outer Diam. Ø 6,40 (±0,20) mm. Outdoor Use. Flame Retardant, Halogen Free and UV, Chemical, Oil and water Resistant.
- B:** Shielding O.F.C. tinned copper Braid covering 85% + O.F.C. tinned copper Drain Wire.
- C:** Waste filler between conductors and total taping in not woven polyester.
- D:** Core Insulation with PPE, colored one Red and one Blue. Diam. Ø 2,00 (±0,20) mm.
- E:** O.F.C. tinned copper formation 16x0,20 mm. Nom. Cross section 2x0,50 mm².

MARKING **tasker®** TSK 1039 PUR 2x0,50 – 20AW - O.F.C. PUR+H.F. + FirestoP® OUTDOOR USE DIGITAL 110 OHM DMXAUDIO CABLE - ITALY

CUSTOM PRODUCTION This product may be custom produced also in **L.S.Z.H.** polymer, **PE, PVC**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	38,00 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	62 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-40/+80°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 29.04.19
	X	Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			