

## Technical Datasheet

**tasker® C288 – 4x2,50 mm<sup>2</sup>**

**Flexible PVC Speaker Cable**  **RoHS<sub>3</sub>**



**CATEGORY** Flexible Speaker Cable (See Audio Catalogue)  
**APPLICATIONS** Professional loudspeakers and premade cables

- A:** Soft **PVC** Sheath. - available in different color.  
Outer cable Diam. Ø 10,80 (±0,20) mm.
- B:** Core Insulation with PVC Sheath, colored one Red, Black, Blue and Green. Diam. Ø 3,50 (±0,20) mm.
- C:** O.F.C. red copper formation 80x0,20 mm.  
Nom. Cross section 4x2,50 mm<sup>2</sup>.

**MARKING** **tasker®** C288 - 4x2,50 mm<sup>2</sup> - O.F.C. - Loudspeakers Cable – Made in Italy  
**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

### Cable Properties

|                       |           |
|-----------------------|-----------|
| Conductor Resistance  | 6,41 Ω/Km |
| Max Rated Voltage     | 49 V      |
| Operative Temperature | -15/+70°C |

| USE     | X | Indoor                | Interno Edificio  | INSTALLATION | X | Fixed                | Fissa            | INFORMATION  | X | RoHS2 Compliant   |
|---------|---|-----------------------|-------------------|--------------|---|----------------------|------------------|--------------|---|-------------------|
| Impiego |   | Outdoor Limited       | Esterno Limitato  | Posa         | X | Restricted Mobile    | Mobile Limitata  | Informazioni | X | Ver. A / 16.05.16 |
|         |   | Outdoor               | Esterno           |              |   | Mobile               | Mobile           |              |   |                   |
|         |   | Outdoor Direct Burial | Esterno Interrato |              |   | Mobile in Drag Chain | Mobile in Catena |              |   |                   |