

Technical Datasheet

tasker® TSK 1038 PUR -2x0,35 mm²



DMX Digital Audio 110 Ohm Cable AES/EBU – Outdoor Use



A

B

C

D

E

CATEGORY Digital Audio Cable (See Audio Catalogue)

APPLICATIONS Digital Audio Applications and DMX Light

- A:** Black **PUR** sheath. Outer Diam. Ø 6,10 (±0,20) mm. Outdoor Use. Flame Retardant, Halogen Free and UV, Chemical, Oil and water Resistant.
- B:** Shielding O.F.C. tinned copper Braid covering 85% + O.F.C. tinned copper Drain Wire.
- C:** Waste filler between conductors and total taping in not woven polyester.
- D:** Core Insulation with PPE, colored one Red and one Blue. Diam. Ø 1,60 mm (±0,20) mm.
- E:** O.F.C. tinned copper formation 11x0,20 mm. Nom. Cross section 2x0,35 mm².

MARKING

tasker® TSK 1038 PUR 2x0,35 – 22AWG - O.F.C. PUR+H.F. + FirestoP® OUTDOOR USE DIGITAL 110 OHM DMXAUDIO CABLE - ITALY

CUSTOM PRODUCTION

This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PVC**, with or without Metallic Armor.

Cable Properties

Conductor Resistance	58,00 Ω/Km
Capacity Core/Core	55 pF/m
Capacity Core/Shield	62 pF/m
Impedance	110 Ω
Max Rated Voltage	49 V
Operative Temperature	-40/+80°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS3 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. B / 29.04.19
	X	Outdoor	Esterno		X	Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			