

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Firestop®

Technical Datasheet

tasker® N07V-250 – 1x2,50 mm²

Power Cable 450/750 V



CATEGORY Power Cable (See Electronics Catalogue)

APPLICATIONS Energy and electrical installation.

A: Flame Retardant **PVC** Sheath with low emission of corrosive gasses.
 Available in different colors.
 Outer cable diam. Ø 3,60 (±0,20) mm.

B: O.F.C. red copper formation with 0,25 mm elementary wire.
 Nom. Cross section 1x2,50 mm².

MARKING N07V-K 450/750V IEMMEQU <HAR>

Cable Properties

Conductor Resistance	7,98 Ω/Km
Max Rated Voltage U₀/U	450/750 V
Min. bending Radius:	4x O.D.
Max Temp. of Short Circuit	160°C/5 sec.
Operative Temperature	+5/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			