

Technical Datasheet

tasker® T25 – 2x12 AWG - Flexible Loudspeaker Cable



CATEGORY Flexible Speaker Cable (See Audio Catalogue)
APPLICATIONS Professional Loudspeakers and premade cables. Not for power supply.

- A:** Black **Flame Retardant PVC** Sheath.
Outer cable Diam. Ø 9,50 (±0,20) mm.
- B:** Core Insulation with **PVC**, colored one Red and one Black.
Diam. Ø 3,70 (±0,20) mm.
- C:** O.F.C. red copper formation 68x0,25 mm.
Nom. Cross section 2x12 AWG.

MARKING tasker® T25 - 2x12 AWG - O.F.C. Loudspeaker Cable - FirestoP® - Made In Italy
CUSTOM This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**,
PRODUCTION with or without Metallic Armor.

Cable Properties

Conductor Resistance	4,31 Ω/Km
Max Rated Voltage	49 V
Operative Temperature	-20/+70°C

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego		Outdoor Limited	Esterno Limitato	Posa	X	Restricted Mobile	Mobile Limitata	Informazioni	X	Ver. A /03.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			