

MILAN S.r.l. a socio unico

Head Office – Export department:
 Viale Europa, 74
 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158
 F. +39 02 9039.4551
 www.taskercables.com

Ufficio Commerciale e Centro Distribuzione
 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy
 T. +39 02 9039.0037-0059
 F. +39 02 9039.0049
 www.tasker.it

Technical Datasheet

tasker® TSK 1071Super – Komby Cable 1xRG58 CU (50Ω) +2x0,50 mm²

FirestoP®


RoHS₂
 2002/95/EC
 2011/65/UE



CATEGORY Komby Cable 50Ω (See Data Network Catalogue)
APPLICATIONS Digital Cameras, Video surveillance and Motorized Antennas.

A: Grey Soft **Flame Retardant PVC** sheath.
 Outer Diam. Ø 10,20 (± 0,20) mm.

RG58CU MIL. C17 F Standard (50 ohm)

- B:** Black PVC Sheath.
Diam. Ø: 5,00 (± 0,20) mm.
- C:** Braid Shielding in O.F.C. tinned copper covering 98%.
- D:** Insulation in compact PE. Diam. Ø 3,00 (± 0,20) mm.
- E:** O.F.C. tinned copper Stranded formation 19x0,18 mm.
Nom. Cross section 1x0,48 mm².

Insulated cores:

- F:** Grey Soft **Flame Retardant PVC** sheath. Colored one white and one red.
Diam. Ø: 2,00 (± 0,20) mm.
- G:** Stranded formation in O.F.C. tinned copper of 16x0,20 mm.
Nom. Cross section 2x0,50 mm².

MARKING **tasker®** TSK 1071 Super 1x50 Ohm + 2x0,50 mm² Special coax Mil. Cable
 FirestoP® MADE IN ITALY

MILAN S.r.l. a socio unico

Head Office – Export department: **Ufficio Commerciale e Centro Distribuzione**
 Viale Europa, 74 Viale Europa 72 Strada F12
 20090 Cusago (MI) Italy 20090 Cusago (MI) Italy
 T. +39 02 9039.4556-4158 T. +39 02 9039.0037-0059
 F. +39 02 9039.4551 F. +39 02 9039.0049
 www.taskercables.com www.tasker.it

CUSTOM PRODUCTION This product may be custom produced also with **L.S.Z.H.** polymer, **PE** or **PUR** sheath, with or without Metallic Armor.

General properties

0,50 mm² Conductors	38 Ω/Km
Coax Conductor Resistance	40 Ω/Km
Impedence	50 Ω
Capacity Core/Shield	100 pF/m
Operative Temperature	-20/+70°C

Attenuation dB/100 m.

100 MHz	25,8
200 MHz	38,2
400 MHz	54,9
800 MHz	77,0
1000 MHz	87,5

USE	X	Indoor	Interno Edificio	INSTALLATION	X	Fixed	Fissa	INFORMATION	X	RoHS2 Compliant
Impiego	X	Outdoor Limited	Esterno Limitato	Posa	X	Flexible Limited	Flessibilità limitata	Informazioni	X	Ver. A / 09.11.15
		Outdoor	Esterno			Dynamic (Drag Chain)	Mobile in Catena			
		Outdoor Direct Burial	Esterno Interrato			Dynamic (Torsion)	Mobile in Torsione			