

## Technical Datasheet

### tasker® TSK1113 - 2x1,50 mm<sup>2</sup> - Shielded Speaker Cable



A	B	C	D
---	---	---	---

**CATEGORY** Shielded Speaker Cable (See Audio Catalogue)  
**APPLICATIONS** Professional Loudspeakers and premade cables

- A:** Black Soft Flame Retardant PVC.  
Outer cable Diam. Ø 8,10 (±0,20) mm.
- B:** Shielding in O.F.C. red copper braid, covering 85%.
- C:** The cores are stranded in a pair with waste filler between conductors and wrapped with not woven polyester based tape.  
Core Insulation with a compact PE, colored one Red and one Black  
Diam. Ø 2,80 (±0,20) mm.
- D:** O.F.C. red copper formation 48x0,20 mm.  
Nom. Cross section 2x1,50 mm<sup>2</sup>.

**MARKING** **tasker®** TSK1113 2x1,50 – 16 AWG O.F.C. Shielded Speaker Cable  
FirestoP® - Italy

**CUSTOM PRODUCTION** This product may be custom produced also in **L.S.Z.H.** polymer, **PE**, **PUR**, with or without Metallic Armor.

#### Cable Properties

<b>Conductor Resistance</b>	12,50 Ω/Km
<b>Max Rated Voltage</b>	49 V
<b>Operative Temperature</b>	-20/+70°C

<b>USE</b>	<b>X</b>	Indoor	Interno Edificio	<b>INSTALLATION</b>	<b>X</b>	Fixed	Fissa	<b>INFORMATION</b>	<b>X</b>	RoHS2 Compliant
<b>Impiego</b>	<b>X</b>	Outdoor Limited	Esterno Limitato	<b>Posa</b>	<b>X</b>	Restricted Mobile	Mobile Limitata	<b>Informazioni</b>	<b>X</b>	Ver. A / 16.05.16
		Outdoor	Esterno			Mobile	Mobile			
		Outdoor Direct Burial	Esterno Interrato			Mobile in Drag Chain	Mobile in Catena			